Warehouse PUMP OFFERS

	1
KIESEL IP03 IMPELLER PUMP with Cable Remote & Trolley	Delivery Rate: 2,000 - 5,000 Lt/Hr Drive Power: .75kW 240v Speed: Variable
IP03M05BS/CR	Motor Speed: Variable, Bypass: Internal
KIESEL IP03 IMPELLER PUMP with Trolley and Cable Remote	Delivery Rate: 2,000 - 5,000 Lt/Hr Drive Power: .75kW 240v (single Phase) Speed: Variable
IP03G05S/CR	Motor Speed: Variable, Bypass: No
KIESEL IP15 IMPELLER PUMP with Trolley IP15VF	Delivery Rate: 7,500 -15,000 Lt/Hr Drive Power: 1.4 - 2.2kW 415v (three phase) Speed: Variable Motor Speed: 700 - 1400 RPM, Bypass: No
KIESEL IP30 IMPELLER PUMP with VFD mounted on Trolley Handle	Delivery Rate: 6,000 - 28,000 Lt/Hr Drive Power: 5.5kW 415v (three phase) Speed: Variable
IP30G06	Motor Speed: 700 - 1400 RPM, Bypass: No
KIESEL IP03 IMPELLER PUMP with Cable Remote & Trolley	Delivery Rate: 2,000 - 5,000 Lt/Hr Drive Power: .75kW 415v Speed: Variable
IP03M05B/CR	Motor Speed: Variable, Bypass: Internal
KIESEL IP03 IMPELLER PUMP with Cable Remote & Trolley	Delivery Rate: 2,000 - 5,000 Lt/Hr Drive Power: .75kW 240v Speed: Variable
IP03M05BS/CR	Motor Speed: Variable, Bypass: Internal
KIESEL IP10 IMPELLER PUMP with Trolley	Delivery Rate: 10,000 Lt/Hr Drive Power: 1.5kW 415v (three phase) Speed: Fixed Motor Speed: 1400 RPM , Bypass: No
KIESEL IP10 IMPELLER PUMP with Trolley	Delivery Rate: 10,000 Lt/Hr Drive Power: 1.5kW 415v (three phase) Speed: Forward/Reverse Motor Speed: 1400 RPM, Bypass: Yes
	Remote: Cable
KIESEL IP10 IMPELLER PUMP with Trolley IP10VFB/CR	Delivery Rate: 5,000-10,000 Lt/Hr Drive Power: 1 - 1.9kW 415v (three phase) Speed: Variable Motor Speed: 700 - 1400 RPM, Bypass: Yes
KIESEL IP20 IMPELLER PUMP with Trolley	Delivery Rate: 20,000 Lt/Hr Drive Power: 4kW 415v (three phase) Speed: Fixed
IP20	Motor Speed: 1400 RPM, Bypass: No
KIESEL IP20 IMPELLER PUMP with Trolley	Remote: Cable Delivery Rate: 10,000 - 20,000 Lt/Hr Drive Power: 2.5 - 4.2kW 415v (three phase)
IP20VF/CR	Speed: Variable Motor Speed: 700 - 1400 RPM, Bypass: No
KIESEL SP05 M Series Eccentric screw pump	Cable Remote: Yes Delivery Rate: 840 - 8,100 Lt/Hr Drive Power: 2.2kW 415v (three phase)
P05M05VFB/CR	Speed: Variable Motor Speed: 700 - 1400RPM , Bypass: Yes



grapeworks NZ

KIESEL SP 12 FTF 06 Series Open Throat Eccentric screw pump, Control Box and mounted on wheels	Delivery Rate: 1,600 - 12,000 Lt/hr Drive Power: 4kW Speed: Variable Hopper opening: 700 x 850mm Hopper volume (approx.): 88Lt Length: 1567mm
SP12FTF06	Height (top of Hopper): 470mm, Height (top of handle) 1129mm, Width: 960mm
KIESEL SP 20 FTF 06 Series Open Throat Eccentric screw pump, Control Box and mounted on wheels	Delivery Rate: 7,000 - 50,000 Lt/hr Drive Power: 7.5kW Speed: Variable Hopper opening: 1100 x 1270mm Hopper volume (approx.): 214Lt Length: 2026mm
SP20FTF06	Height (top of Hopper): 540mm Height (top of handle): 1139mm Width: 1270mm

CAZAUX LOB 300 PREMIUM LOBE PUMP CAZ-LOB300PREMIUM	BSM FITTINGS & VFD
CAZAUX LOB 450 PREMIUM LOBE PUMP - 5,000 - 45,000 L/h - 7.5 kW - BSM FITTINGS & VFD CAZ-LOB450PREMIUM	Included in the premium pack: Wireless remote control (Start/Stop, Speed and directions) Pressure switch and Vacuum switch Quick motorized valve 4 Wheel Trolley"
CAZAUX LOB 450 PREMIUM LOBE PUMP - 5,000 - 45,000 L/h - 7.5 kW - BSM FITTINGS & VFD CAZ-LOB450PREMIUM	Included in the premium pack : Wireless remote control (Start/Stop, Speed and directions) Pressure switch and Vacuum switch Quick motorized valve 4 Wheel Trolley
CAZ-AEROSMOOTH	CAZAUX AEROSMOOTH CO2 Pumpover System
CAZAUX LCE5/140 LOW SPEED IMPELLER PUMP	WITH VFD, TROLLEY & 20m CABLE REMOTE - 500 - 14000 L/H 1.5kW - 38mm BSM INLET/OUTLET
CAZ-LCE5/140-CR	

ENOITALIA EURO 30 SINGLE PHASE IMPELLER PUMP	With VFD on trolley, Stainless Steel 4 Wheel Trolley, Cable emote & 38mm BSM male fittings
ENO-EUR030-S	
ENOITALIA EURO 30 THREE PHASE IMPELLER PUMP	With VFD on trolley, Stainless Steel 4 Wheel Trolley, Cable Remote & 38mm BSM male fittings
ENO-EURO30-T	
ENOITALIA Phoenix 18 Atex rated diaphragm pump ENO-PHOENIX18	 Fluid Connection: 1/2" "Triclover Air Connection: 6mm Max Flow Rate: 20 lt/min Max Air Pressure: 7 Bar Max Delivery Head: 70mt Max Suction Lift Dry: 5 mt Max Suction Lift Wet: 9.8mt
ENOITALIA Phoenix 30 Atex rated diaphragm pump ENO-PHOENIX30	 Max Solid Passing: 2.5mm Fluid Connection: 1/2" Triclover Air Connection: 6mm Max Flow Rate: 35 lt/min Max Air Pressure: 7 Bar Max Delivery Head: 70mt Max Suction Lift Dry: 6 mt Max Suction Lift Wet: 9.8mt Max Solid Passing: 3mm

For more details and pricing call: Australia: 03 9555 5500 | New Zealand: 04 390 3577