

Semi Auto labeller – Cylindrical

Label Applicators are the perfect semi-automatic labeling solution for cylindrical containers including bottles, cans, jars.

With a Label Applicator you'll apply labels faster and more accurately, helping to speed up your production, speeds of up to 1200 per hour

Labels are perfectly applied without wrinkles, giving your finished products a highly professional look.

It can apply one or two different labels to a single container. A built-in **LED counter and memory** for up to nine front-to-back label offsets is also included.

Set-up and operation is fast and easy:

- Set the guides
- Place your container in the machine
- Press the footswitch and your label is applied

The built-in spring-loaded pressure arm makes sure labels are applied firmly and without wrinkles.



Features:

- Quick set-up and easy operation
- Accurately applies labels to the front and back with variable spacing
- Fast – labels are applied at 135mm per second – up to 1200 containers per hour
- Compact size – fits on most desks and countertops
- Industrial strength – built with heavy-duty sheet metal and steel for long life

What's in the Box:

- A power cord and power adapter, label roll bar and guides, and an Operator's Guide.

Specifications:

Container Height:	25.4mm to 238mm
Container Diameter:	15mm to 170mm
Container Shape:	Cylindrical
Supply roll diameter:	203mm
Media liner width:	25.4mm to 213mm (Labels to be within this sizing)
Supply roll core:	51.8mm to 76.2mm
Electrical rating:	12VDC, 5.0A
Power requirements:	100-240VAC, 50/60 Hz, 60 watts
Weight:	7.26 kg
Labeller Dimensions:	340mmW x 226mmH x 328mmD
Gap between Labels:	Recommended: 3.175 mm - 6.35 mm
Label Type:	Die cut with waste removed. Clear labels can be used.
Liner Thickness:	2 mil – 10 mil (smoothness will affect feeding – (too slippery or too thin will slip through the drive rollers)
Label + Adhesive Thickness:	5 mil - 15 mil
Wind Direction	Wound out - Position 3 or 4 for most containers)